



(Optional D) Open Area Ratio Target	
150 %	
200 %	
250 %	
300 %	
<b>OR</b> – Use length (D) below	

Standard Cap Diameters (B)	
100 mm	
115 mm	
132 mm	
145 mm	
160 mm	
175 mm	
260 mm	
Custom see below	
<b>OR</b>	

Custom Cap (B)	
O.D. mm	

Cap	
Solid	Perforated

Screen Removal Size	

Material	
304 S/S	316 S/S

Standard Flange Details	
Size	
Type (e.g. ANSI)	
<b>OR</b>	
Custom Flange	
<b>C</b>	mm
<b>T</b>	mm
<b>P.C.D.</b>	mm
<b>Hole</b>	mm
<b>No. of Holes</b>	

Dimensions (mm)	
<b>A</b>	mm
<b>D</b>	mm

Please complete, save as a PDF and return for quoting.

**Return to:**  
sales@monarcindustrial.com.au



	DWG-01022	<b>Title:</b>	Flanged Suction Strainer in Stainless Steel
<b>Date:</b>		<b>Name:</b>	
<b>Monarch Ref No.</b>		<b>Company:</b>	
<b>Customer Ref No.</b>		<b>Email:</b>	
NOT TO SCALE		<b>Phone:</b>	